

BUILDING SYSTEMS ANALYSIS AND RETROFIT MANUAL



**SHEET METAL AND AIR CONDITIONING CONTRACTORS'
NATIONAL ASSOCIATION, INC.**
www.smacna.org

BUILDING SYSTEMS ANALYSIS AND RETROFIT MANUAL

SECOND EDITION – MARCH, 2011



**SHEET METAL AND AIR CONDITIONING CONTRACTORS'
NATIONAL ASSOCIATION, INC.**

4201 Lafayette Center Drive
Chantilly, VA 20151-1219
www.smacna.org

BUILDING SYSTEMS ANALYSIS AND RETROFIT MANUAL

COPYRIGHT © SMACNA 2011
All Rights Reserved
by

**SHEET METAL AND AIR CONDITIONING CONTRACTORS'
NATIONAL ASSOCIATION, INC.**

4201 Lafayette Center Drive
Chantilly, VA 20151-1219

Printed in the U.S.A.

FIRST EDITION – OCTOBER 1995
SECOND EDITION – MARCH 2011

Except as allowed in the Notice to Users and in certain licensing contracts, no part of this book may be reproduced, stored in a retrievable system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of the publisher.

FOREWORD

This second edition updating and revision of the Retrofit manual comes at a time when green building guidelines, standards and codes are either recently finished or nearing completion. These guidelines, standards and codes are markers on the road to a sea change toward new approaches in new building construction. While these new green guidelines, standards and codes also apply to major renovation of existing buildings the focus is on new construction and little has been published to address the much larger issue of energy efficiency in existing buildings.

Historically, new buildings have added less than two percent to the total inventory of commercial buildings in the United States on an annual basis. For meaningful energy use reductions to occur on a national scale, the energy efficiency of thousands of existing buildings must be improved significantly. For the United States to make major progress in reducing its national energy consumption, most, if not all of the existing buildings must use far less energy.

Characteristics of all the green codes and standards are that public transportation be accessible nearby and that new land—greenfields—development is discouraged. Existing buildings are often located near public transportation and development typically occurs on a building’s existing footprint. These two “greening” drivers may combine with basic economic factors to produce a compelling incentive for many prospective building owners to choose renovation of an existing building over the construction of new facilities.

The other factors that will help drive the retrofit and upgrade of existing buildings is the rising cost of energy and fuel. As other countries compete more fervently for the world’s available fuels, higher prices are inevitable. Payback periods and return on investment intervals will shrink sufficiently to more easily justify capital outlays on the most energy efficient buildings; resulting in modifications to building envelopes, HVAC, plumbing and electrical systems.

The members of the *Building Systems Analysis and Retrofit Manual* task force have shared their expertise in the belief that other contractors will consider and enter the promising field of retrofitting and upgrading existing buildings. Readers of this manual are encouraged to submit additional thoughts and ideas to SMACNA’s Technical Resources staff to further add to the building science and art presented in this manual.

SHEET METAL AND AIR CONDITIONING CONTRACTORS’
NATIONAL ASSOCIATION, INC.



BUILDING SYSTEMS ANALYSIS AND RETROFIT TASK FORCE

Christopher A. Fulton
Bright Sheet Metal Co., Inc.
Indianapolis, IN

Dave Hill
France Mechanical Corporation
Edwardsville, IL

Gene Darby
Environmental Mechanical Contractors, Inc.
Olathe, KS

Russ Kimball
Evergreen State Heat & AC
Everett, WA

Peyton Collie, *Staff*
SMACNA
Chantilly, VA



NOTICE TO USERS OF THIS PUBLICATION

1. DISCLAIMER OF WARRANTIES

a) The Sheet Metal and Air Conditioning Contractors' National Association ("SMACNA") provides its product for informational purposes.

b) The product contains "Data" which is believed by SMACNA to be accurate and correct but the data, including all information, ideas and expressions therein, is provided strictly "AS IS," with all faults. SMACNA makes no warranty either express or implied regarding the Data and SMACNA EXPRESSLY DISCLAIMS ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE.

c) By using the data contained in the product user accepts the Data "AS IS" and assumes all risk of loss, harm or injury that may result from its use. User acknowledges that the Data is complex, subject to faults and requires verification by competent professionals, and that modification of parts of the Data by user may impact the results or other parts of the Data.

d) IN NO EVENT SHALL SMACNA BE LIABLE TO USER, OR ANY OTHER PERSON, FOR ANY INDIRECT, SPECIAL OR CONSEQUENTIAL DAMAGES ARISING, DIRECTLY OR INDIRECTLY, OUT OF OR RELATED TO USER'S USE OF SMACNA'S PRODUCT OR MODIFICATION OF DATA THEREIN. This limitation of liability applies even if SMACNA has been advised of the possibility of such damages. IN NO EVENT SHALL SMACNA'S LIABILITY EXCEED THE AMOUNT PAID BY USER FOR ACCESS TO SMACNA'S PRODUCT OR \$1,000.00, WHICHEVER IS GREATER, REGARDLESS OF LEGAL THEORY.

e) User by its use of SMACNA's product acknowledges and accepts the foregoing limitation of liability and disclaimer of warranty and agrees to indemnify and hold harmless SMACNA from and against all injuries, claims, loss or damage arising, directly or indirectly, out of user's access to or use of SMACNA's product or the Data contained therein.

2. ACCEPTANCE

This document or publication is prepared for voluntary acceptance and use within the limitations of application defined herein, and otherwise as those adopting it or applying it deem appropriate. It is not a safety standard. Its application for a specific project is contingent on a designer or other authority defining a specific use. SMACNA has no power or authority to police or enforce compliance with the contents of this document or publication and it has no role in any representations by other parties that specific components are, in fact, in compliance with it.

3. AMENDMENTS

The Association may, from time to time, issue formal interpretations or interim amendments, which can be of significance between successive editions.

4. PROPRIETARY PRODUCTS

SMACNA encourages technological development in the interest of improving the industry for the public benefit. SMACNA does not, however, endorse individual manufacturers or products.

5. FORMAL INTERPRETATION

a) A formal interpretation of the literal text herein or the intent of the technical committee or task force associated with the document or publication is obtainable only on the basis of written petition, addressed to the Technical Resources Department and sent to the Association's national office in Chantilly, Virginia. In the event that the petitioner has a substantive disagreement with the interpretation, an appeal may be filed with the Technical Resources Committee, which has technical oversight responsibility. The request must pertain to a specifically identified portion of the document that does not involve published text which provides the requested information. In considering such requests, the Association will not review or judge products or components as being in compliance with the document or publication. Oral and written interpretations otherwise obtained from anyone affiliated with the Association are unofficial. This procedure does not prevent any committee or task force chairman, member of the committee or task force, or staff liaison from expressing an opinion on a provision within the document, provided that such person clearly states that the opinion is personal and does not represent an official act of the Association in any way, and it should not be relied on as such. The Board of Directors of SMACNA shall have final authority for interpretation of this standard with such rules or procedures as they may adopt for processing same.

b) SMACNA disclaims any liability for any personal injury, property damage, or other damage of any nature whatsoever, whether special, indirect, consequential or compensatory, direct or indirectly resulting from the publication, use of, or reliance upon this document. SMACNA makes no guaranty or warranty as to the accuracy or completeness of any information published herein.

6. APPLICATION

a) Any standards contained in this publication were developed using reliable engineering principles and research plus consultation with, and information obtained from, manufacturers, users, testing laboratories, and others having specialized experience. They are



subject to revision as further experience and investigation may show is necessary or desirable. Construction and products which comply with these Standards will not necessarily be acceptable if, when examined and tested, they are found to have other features which impair the result contemplated by these requirements. The Sheet Metal and Air Conditioning Contractors' National Association and other contributors assume no responsibility and accept no liability for the application of the principles or techniques contained in this publication. Authorities considering adoption of any standards contained herein should review all federal, state, local, and contract regulations applicable to specific installations.

b) In issuing and making this document available, SMACNA is not undertaking to render professional or other services for or on behalf of any person or entity. SMACNA is not undertaking to perform any duty owed to any person or entity to someone else. Any person or organization using this document should rely on his, her or its own judgement or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstance.

7. REPRINT PERMISSION

Non-exclusive, royalty-free permission is granted to government and private sector specifying authorities to reproduce *only* any construction details found herein in their specifications and contract drawings prepared for receipt of bids on new construction and renovation work within the United States and its territories, provided that the material copied is unaltered in substance and that the reproducer assumes all liability for the specific application, including errors in reproduction.

8. THE SMACNA LOGO

The SMACNA logo is registered as a membership identification mark. The Association prescribes acceptable use of the logo and expressly forbids the use of it to represent anything other than possession of membership. Possession of membership and use of the logo in no way constitutes or reflects SMACNA approval of any product, method, or component. Furthermore, compliance of any such item with standards published or recognized by SMACNA is not indicated by presence of the logo.

TABLE OF CONTENTS

TABLE OF CONTENTS

FOREWORD	iii
BUILDING SYSTEMS ANALYSIS AND RETROFIT TASK FORCE	iv
NOTICE TO USERS OF THIS PUBLICATION	v
TABLE OF CONTENTS	vii
CHAPTER 1 INTRODUCTION	Page
1.1 RETROFIT CONTRACTOR REQUIREMENTS	1.1
1.2 RETROFIT MARKET	1.1
1.3 ABOUT THIS MANUAL	1.2
CHAPTER 2 COMMISSIONING	
2.1 INTRODUCTION	2.1
2.2 PROCESS OVERVIEW	2.2
2.3 PRELIMINARY INVESTIGATION	2.3
2.4 SURVEY AND DOCUMENTATION PHASE	2.3
2.5 ANALYSIS	2.6
2.6 MODIFICATIONS	2.6
2.7 COMMISSIONING TESTS	2.6
2.8 DOCUMENTATION AND TRAINING	2.7
CHAPTER 3 ELECTRICAL	
3.1 INTRODUCTION	3.1
3.2 ELECTRICAL REVIEW	3.1
3.3 UTILITY CHARGES	3.3
3.4 EQUIPMENT	3.4
3.5 LIGHTING	3.5
3.6 PEAK DEMAND POWER MANAGEMENT	3.7
3.7 REFERENCES	3.9
CHAPTER 4 BUILDING ENVELOPE	
4.1 INTRODUCTION	4.1
4.2 BUILDING ENVELOPE – ROOF	4.1
4.3 BUILDING ENVELOPE – OUTSIDE DOORS	4.3
4.4 BUILDING ENVELOPE – WINDOWS AND SKYLIGHTS	4.3
4.5 BUILDING ENVELOPE – EXTERIOR WALLS	4.4
4.6 BUILDING ENVELOPE – SLAB	4.4
4.7 BUILDING ENVELOPE – INFILTRATION	4.4
4.8 BUILDING ENVELOPE – JOINTS	4.4
CHAPTER 5 WATER USAGE AND EFFICIENCY	
5.1 INTRODUCTION	5.1
5.2 DOMESTIC HOT WATER	5.1
5.3 FIXTURES	5.4
5.4 RAINWATER HARVESTING	5.5
5.5 REFERENCES	5.5



CHAPTER 6	HVAC SYSTEM	Page
6.1	INTRODUCTION	6.1
6.2	AIR HANDLING SYSTEM	6.1
6.3	COOLING SYSTEM	6.8
6.4	HEATING SYSTEM	6.16
6.5	ENERGY RECOVERY SYSTEMS	6.19
6.6	PARTICULATE AIR FILTRATION	6.22
6.7	REFERENCES	6.22
CHAPTER 7	BUILDING AUTOMATION SYSTEMS AND CONTROLS	
7.1	INTRODUCTION	7.1
7.2	HVAC CONTROL SYSTEMS	7.1
7.3	BUILDING AUTOMATION SYSTEM (BAS)	7.1
7.4	BAS PROTOCOLS	7.2
7.5	BAS CONTROL STRATEGIES AND OPTIMIZATION	7.3
7.6	BUILDING ENERGY MANAGEMENT AND CONTROL SYSTEMS (EMCS)	7.8
7.7	REFERENCES	7.10
CHAPTER 8	CFC AND HCFC CHANGEOUTS	
8.1	INTRODUCTION	8.1
8.2	MONTREAL PROTOCOL AND CLEAN AIR ACT	8.1
8.3	REFRIGERANT MANAGEMENT PLAN	8.2
8.4	CHILLERS	8.2
8.5	RETROFIT OPPORTUNITIES	8.2
8.6	CHANGEOUTS FOR OTHER TYPES OF HVAC EQUIPMENT	8.4
8.7	REFRIGERANT CHANGEOUTS	8.5
CHAPTER 9	CUSTOMER IDENTIFICATION RETROFIT OPPORTUNITY	
9.1	CUSTOMER IDENTIFICATION	9.1
9.2	CUSTOMER CONTACT STRATEGY	9.3
9.3	BUILDING WALKTHROUGH	9.3
9.4	USING THE ENERGY AUDIT TO SELL RETROFIT WORK	9.5
APPENDIX A	SWOT ANALYSIS	
A.1	SWOT ANALYSIS	A.1
APPENDIX B	DEDICATED OUTSIDE AIR SYSTEMS	
B.1	DEDICATED OUTSIDE AIR SYSTEMS OVERVIEW	B.1
B.2	DOAS ADVANTAGES	B.1
B.3	DOAS DISADVANTAGES	B.2
B.4	FRACTIONAL AND INTEGRATED DOAS SYSTEMS	B.2
APPENDIX C	ELECTRIC DEMAND CHARGES	
C.1	INTRODUCTION	C.1
APPENDIX D	THERMAL ENERGY STORAGE	
D.1	FULL OR PARTIAL STORAGE	D.1
APPENDIX E	WALKTHROUGH CHECKLIST	
GLOSSARY		

TABLES

	Page
3-1 Capacitor Correction For Power Factor	3.2
3-2 Utility Block Pricing – Increasing versus Declining	3.3
3-3 Comparison of Lamp Types	3.7
5-1a Plumbing Fixtures - Maximum Water Flow Allowed by Energy Policy Act of 2005 I-P	5.4
5-1b Plumbing Fixtures - Maximum Water Flow Allowed by Energy Policy Act of 2005 SI	5.4
6-1 Chiller Types by Capacity	6.10
6-2 Low Delta-T Causes and Required Actions	6.11
8-1 Montreal and United States Phaseout Schedules	8.1
8-2 Chiller Types by Capacity	8.2
8-3 Long Term Replacement for Common Refrigerants	8.3
A-1 Strengths and Weaknesses – SWOT Analysis	A.1



FIGURES**Page**

3-1	Power Factor Relationships	3.1
4-1	Major Components of Building Envelope	4.2
6-1	Multi-Zone System	6.3
6-2	Single-Fan Dual-Fuct System	6.4
6-3	Typical DOAS System	6.6
6-4	Preconditioning DOAS	6.7
6-5	Separately Ducted DOAS	6.9
6-6	Primary-Only Chilled Water System	6.12
6-7	Primary-Secondary Chilled Water System	6.13
6-8	Chiller Efficiency Loss Vs. %Oil in Refrigerant	6.14
6-9	Condensate Heat Recovery	6.20
6-10	Laundry and Kitchen Hot Water Recovery System	6.21
6-11	Compressor Heat Recovery	6.21
7-1	TES With Bypass Valve for Temperature-Controlled Operation	7.7
7-2	Graph of Operating Loads – Hot/Humid Day	7.7
7-3	Graph of Operating Loads – Warm Day	7.9
7-4	Graph of Operating Loads – Cool Day	7.9



CHAPTER 1

INTRODUCTION

1.1 RETROFIT CONTRACTOR REQUIREMENTS

Contractors interested in the retrofit market should consider taking on the role of general contractor (GC). Building owners will prefer one point of contact and it needs to be the retrofit contractor. The retrofit contractor should arrange for and coordinate any subcontracting work needed to complete all the upgrades of the retrofit project. Many retrofit projects will require drawings that are sealed by a registered professional engineer (PE). If a PE is not employed by your firm, consider establishing a business relationship with one.

The costs of retrofit projects will have to be justified to the owner. Become familiar with return on investment (ROI) and life-cycle cost (LCC) analysis by reading the chapter on that topic in the SMACNA's *Energy Systems Analysis and Management* manual. An excellent resource for computer programs related to building energy and retrofit analysis can be found on the Department of Energy (DOE) website. Use one of the online computer programs to show the owner the impact of recommended retrofits. Keep it simple. Explain and show the operational and reduced maintenance benefits, life-cycle costs, monthly and annual energy or water savings, and return on dollars invested in building upgrades.

1.2 RETROFIT MARKET

The retrofit market is a multibillion dollar opportunity that has great upside potential as building owners become familiar with concepts such as sustainability, green building, energy savings, and commissioning. Take a look at the existing buildings in your community and service area. What is the general age and condition of those buildings?

In the commercial market retrofit opportunities are most likely to arise during or because of the following events: equipment failures, equipment obsolescence, energy savings initiatives, building purchases, tenant improvements, rebuilding, and building renovation.

1.2.1 Equipment Failure

Equipment failure accounts for over 85 percent of the retrofit market. Repairing or replacing equipment is an opportunity to expand into other retrofit opportunities. How the customer perceives the results and is treated will dictate whether this is a one-time or an ongoing business relationship with recurring opportunities.

1.2.2 Equipment Obsolescence

The size of the equipment obsolescence market is unknown since it falls in both categories of equipment failure and energy savings. Equipment obsolescence may be a leaking chiller that uses a CFC refrigerant, it may be a high-energy user like an old multizone system, or it could be a VAV system with failed or poorly functioning pneumatic actuators.

It is unlikely the customer will consult an HVAC contractor specifically about equipment obsolescence. This opportunity is more likely to reveal itself to the retrofit contractor when performing an energy savings walk-through, during an equipment repair, or when replacing equipment or controls due to failure or comfort complaints. There is great opportunity for the retrofit contractor to profit from obsolete equipment if the retrofit contractor trains its staff to recognize equipment that is outdated or inefficient and to bring that to the owners' and contractors attention. Equipment obsolescence is essentially an energy savings retrofit that is identified by the retrofit contractor instead of the customer.

1.2.3 Energy Savings

This accounts for less than 15 percent of the retrofit market but represents one of the areas of greatest potential growth. Approximately 80 percent of owners that have had an HVAC equipment retrofit had the retrofit due to an energy audit or commissioning. Therefore, the retrofit contractor should be familiar with the process of conducting an energy audit and the commissioning process.

1.2.4 Building Purchases

When a building is purchased it is very likely that it will at least undergo changes and possibly substantial upgrades to match the requirements of the new owner. This is a key opportunity for HVAC contractors to meet the new owner and spend a few minutes looking at the facility and offering preliminary suggestions regarding HVAC system enhancements and equipment upgrades. *Note: Certain future Model Building and Energy Codes may mandate an energy audit and commissioning be conducted within one year of the sale of an existing building.*

1.2.5 Tenant Improvements

Tenant improvements are often "invisible" from outside the building. The improvements may be a simple reconfiguration of existing space or the addition of a loading or staging area to serve growing material man-

