BS EN 55016-2-3:2017



BSI Standards Publication

Specification for radio disturbance and immunity measuring apparatus and methods

Part 2-3: Methods of measurement of disturbances and immunity - Radiated disturbance measurements

bsi.

National foreword

This British Standard is the UK implementation of EN 55016-2-3:2017. It is identical to CISPR 16-2-3:2016. It supersedes BS EN 55016-2-3:2010+A2:2014, which will be withdrawn on 20 October 2019.

The UK participation in its preparation was entrusted to Technical Committee GEL/210/11, EMC - Standards Committee.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2018
Published by BSI Standards Limited 2018

ISBN 978 0 580 85583 2

ICS 33.100.20; 33.100.10

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 January 2018.

Amendments/corrigenda issued since publication

Date	Text affected

EUROPEAN STANDARD

NORME EUROPÉENNE

EUROPÄISCHE NORM

EN 55016-2-3

April 2017

ICS 33.100.10; 33.100.20

Supersedes EN 55016-2-3:2010

English Version

Specification for radio disturbance and immunity measuring apparatus and methods - Part 2-3: Methods of measurement of disturbances and immunity - Radiated disturbance measurements (CISPR 16-2-3:2016)

Spécifications des méthodes et des appareils de mesure des perturbations radioélectriques et de l'immunité aux perturbations radioélectriques - Partie 2-3: Méthodes de mesure des perturbations et de l'immunité - Mesures des perturbations rayonnées (CISPR 16-2-3:2016)

Anforderungen an Geräte und Einrichtungen sowie Festlegung der Verfahren zur Messung der hochfrequenten Störaussendung (Funkstörungen) und Störfestigkeit - Teil 2-3: Verfahren zur Messung der hochfrequenten Störaussendung (Funkstörungen) und Störfestigkeit - Messung der gestrahlten Störaussendung (CISPR 16-2-3:2016)

This European Standard was approved by CENELEC on 2016-10-20. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

© 2017 CENELEC All rights of exploitation in any form and by any means reserved worldwide for CENELEC Members.

European foreword

The text of document CISPR/A/1176A/FDIS, future edition 4 of CISPR 16-2-3, prepared by CISPR SC A "Radio-Interference measurements and statistical methods" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 55016-2-3:2017.

The following dates are fixed:

• latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement	(dop)	2017-10-28
• latest date by which the national standards conflicting with the document have to be withdrawn	(dow)	2020-04-28

This document supersedes EN 55016-2-3:2010.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard CISPR 16-2-3:2016 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

CISPR 11:2015	NOTE	Harmonized as EN 55011:2016.
CISPR 16-1-6:2014	NOTE	Harmonized as EN 55016-1-6:2015.
CISPR 22:2008	NOTE	Harmonized as EN 55022:2010.
IEC 61140:2016	NOTE	Harmonized as EN 61140:2016.
ISO/IEC Guide 2:2004	NOTE	Harmonized as EN 45020:2006.
ISO/IEC 17000:2004	NOTE	Harmonized as EN ISO/IEC 17000:2004.
IEC 61000-4-21	NOTE	Harmonized as EN 61000-4-21.

Annex ZA
(normative)
Normative references to international publications with their corresponding European publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 When an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu.

Publication	Year	Title	EN/HD	Year
IEC 60050-161	-	International Electrotechnical Vocabulary (IEV) -- Chapter 161: Electromagnetic compatibility	-	-
IEC 61000-4-3	2006	Electromagnetic compatibility (EMC) -- Part 4-3: Testing and measurement techniques - Radiated, radio-frequency, electromagnetic field immunity test	EN 61000-4-3	2006
+ A1	2007		+ A1	2008
+ A2	2010		+ A2	2010
IEC 61000-4-20	-	Electromagnetic compatibility (EMC) -- Part 4-20: Testing and measurement techniques - Emission and immunity testing in transverse electromagnetic (TEM) waveguides	EN 61000-4-20	
CISPR 14-1	2016	Electromagnetic compatibility - Requirements for household appliances, electric tools and similar apparatus - Part 1: Emission	FprEN 55014-1	2016
CISPR 16-1-1	-	Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-1: Radio disturbance and immunity measuring apparatus - Measuring appartus	-	-
CISPR 16-1-2	2014	Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-2: Radio disturbance and immunity measuring apparatus - Coupling devices for conducted disturbance measurements	EN 55016-1-2	2014
CISPR 16-1-4	2010	Specification for radio disturbance and immunity measuring apparatus and methods -- Part 1-4: Radio disturbance and immunity measuring apparatus - Antennas and test sites for radiated disturbance measurements	EN 55016-1-4	2010
+ A1	2012		+ A1	2012
CISPR 16-2-1	2014	Specification for radio disturbance and immunity measuring apparatus and methods - Part 2-1: Methods of measurement of disturbances and immunity - Conducted disturbance measurements	EN 55016-2-1	2014
CISPR 16-4-2	-	Specification for radio disturbance and immunity measuring apparatus and methods -- Part 4-2: Uncertainties, statistics and limit modelling - Measurement instrumentation uncertainty	EN 55016-4-2	

CISPR TR 16-4-1	-	Specification for radio disturbance and immunity measuring apparatus and methods - Part 4-1: Uncertainties, statistics and limit modelling - Uncertainties in standardized EMC tests	-	-
CISPR TR 16-4-5	-	Specification for radio disturbance and immunity measuring apparatus and methods - Part 4-5: Uncertainties, statistics and limit modelling - Conditions for the use of alternative test methods	-	-

CONTENTS

FOREWORD....7
1 Scope....9
2 Normative references....9
3 Terms, definitions and abbreviations....10
3.1 Terms and definitions....10
3.2 Abbreviated terms....15
4 Types of disturbance to be measured....16
4.1 General....16
4.2 Types of disturbance....16
4.3 Detector functions....16
5 Connection of measuring equipment....16
6 General measurement requirements and conditions....17
6.1 General....17
6.2 Disturbance not produced by the equipment under test....17
6.2.1 General....17
6.2.2 Compliance (conformity assessment) testing....17
6.3 Measurement of continuous disturbance....17
6.3.1 Narrowband continuous disturbance....17
6.3.2 Broadband continuous disturbance....17
6.3.3 Use of spectrum analyzers and scanning receivers....17
6.4 EUT arrangement and measurement conditions....18
6.4.1 General arrangement of the EUT....18
6.4.2 Operation of the EUT....20
6.4.3 EUT time of operation....20
6.4.4 EUT running-in time....21
6.4.5 EUT supply....21
6.4.6 EUT mode of operation....21
6.4.7 Operation of multifunction equipment....21
6.4.8 Determination of arrangement(s) causing maximum emissions....21
6.4.9 Recording of measurements....21
6.5 Interpretation of measuring results....22
6.5.1 Continuous disturbance....22
6.5.2 Discontinuous disturbance....22
6.5.3 Measurement of the duration of disturbance....22
6.6 Measurement times and scan rates for continuous disturbance....22
6.6.1 General....22
6.6.2 Minimum measurement times....23
6.6.3 Scan rates for scanning receivers and spectrum analyzers....23
6.6.4 Scan times for stepping receivers....24
6.6.5 Strategies for obtaining a spectrum overview using the peak detector....25
6.6.6 Timing considerations using FFT-based instruments....29
7 Measurement of radiated disturbances....32
7.1 Introductory remarks....32
7.2 Loop-antenna system measurements (9 kHz to 30 MHz)....33
7.2.1 General....33
7.2.2 General measurement method....33

7.2.3 Test environment 34
7.2.4 Configuration of the equipment under test 35
7.2.5 Measurement uncertainty for LAS 35
7.3 Open-area test site or semi-anechoic chamber measurements (30 MHz to 1 GHz) 35
7.3.1 Measurand 35
7.3.2 Test site requirements 38
7.3.3 General measurement method 38
7.3.4 Measurement distance 39
7.3.5 Antenna height variation 40
7.3.6 Product specification details 40
7.3.7 Measurement instrumentation 42
7.3.8 Field-strength measurements on other outdoor sites 42
7.3.9 Measurement uncertainty for OATS and SAC 42
7.4 Fully-anechoic room measurements (30 MHz to 1 GHz) 42
7.4.1 Test set-up and site geometry 42
7.4.2 EUT position 45
7.4.3 Cable layout and termination 46
7.4.4 Measurement uncertainty for FAR 47
7.5 Radiated emission measurement method (30 MHz to 1 GHz) and radiated immunity test method (80 MHz to 1 GHz) with common test set-up in semi-anechoic chamber 47
7.5.1 Applicability 47
7.5.2 EUT perimeter definition and antenna-to-EUT separation distance 47
7.5.3 Uniform test volume 48
7.5.4 Specifications for EUT set-up in common emissions/immunity test set-up 49
7.5.5 Measurement uncertainty for common emission/immunity set-up and method 55
7.6 Fully-anechoic room and absorber-lined OATS/SAC measurements (1 GHz to 18 GHz) 55
7.6.1 Quantity to measure 55
7.6.2 Measurement distance 55
7.6.3 Set-up and operating conditions of the equipment under test (EUT) 56
7.6.4 Measurement site 56
7.6.5 Measurement instrumentation 56
7.6.6 Measurement procedure 57
7.6.7 Measurement uncertainty for FAR 63
7.7 *In situ* measurements (9 kHz to 18 GHz) 64
7.7.1 Applicability of and preparation for *in situ* measurements 64
7.7.2 Field-strength measurements *in situ* in the frequency range 9 kHz to 30 MHz 65
7.7.3 Field-strength measurements *in situ* in the frequency range above 30 MHz 65
7.7.4 *In situ* measurement of the disturbance effective radiated power using the substitution method 66
7.7.5 Documentation of the measurement results 70
7.7.6 Measurement uncertainty for *in situ* method 70
7.8 Substitution measurements (30 MHz to 18 GHz) 70
7.8.1 General 70
7.8.2 Test site 71

7.8.3 Test antennas 71
7.8.4 EUT configuration 72
7.8.5 Test procedure 72
7.8.6 Measurement uncertainty for substitution method 72
7.9 Reverberation chamber measurements (80 MHz to 18 GHz) 72
7.10 TEM waveguide measurements (30 MHz to 18 GHz) 72
8 Automated measurement of emissions 72
8.1 Introduction – Precautions for automated measurements 72
8.2 Generic measurement procedure 73
8.3 Pre-scan measurements 73
8.3.1 General 73
8.3.2 Determination of the required measurement time 74
8.3.3 Pre-scan requirements for different types of measurements 74
8.4 Data reduction 75
8.5 Emission maximization and final measurement 76
8.6 Post-processing and reporting 77
8.7 Emission measurement strategies with FFT-based measuring instruments 77
Annex A (informative) Measurement of disturbances in the presence of ambient emissions 78
A.1 General 78
A.2 Terms and definitions 78
A.3 Problem description 78
A.4 Proposed solution 78
A.4.1 Overview 78
A.4.2 Pre-testing the EUT in a shielded room 81
A.4.3 Method of measurement of EUT disturbances in the presence of narrowband ambient emissions 82
A.4.4 Method of measurement of EUT disturbance in the presence of broadband ambient emissions 85
A.5 Determination of the EUT disturbance in case of superposition 87
Annex B (informative) Use of spectrum analyzers and scanning receivers 92
B.1 General 92
B.2 Overload 92
B.3 Linearity test 92
B.4 Selectivity 92
B.5 Normal response to pulses 92
B.6 Peak detection 92
B.7 Frequency scan rate 93
B.8 Signal interception 93
B.9 Average detection 93
B.10 Sensitivity 93
B.11 Amplitude accuracy 94
Annex C (informative) Scan rates and measurement times for use with the average detector 95
C.1 Purpose 95
C.2 Suppression of disturbances 95
C.2.1 Suppression of impulsive disturbance 95
C.2.2 Suppression of impulsive disturbance by digital averaging 96
C.2.3 Suppression of amplitude modulation 96

C.3 Measurement of slowly intermittent, unsteady or drifting narrowband disturbances 96
C.4 Recommended procedure for automated or semi-automated measurements 98
Annex D (informative) Explanation of the APD measurement method applying to the compliance test 99
Annex E (normative) Determination of suitability of spectrum analyzers for compliance tests 101
Bibliography 102

Figure 1 – Measurement of a combination of a CW signal (NB) and an impulsive signal (BB) using multiple sweeps with maximum hold 26
Figure 2 – Example of a timing analysis 27
Figure 3 – A broadband spectrum measured with a stepped receiver 28
Figure 4 – Intermittent narrowband disturbances measured using fast short repetitive sweeps with maximum hold function to obtain an overview of the emission spectrum 29
Figure 5 – FFT scan in segments 31
Figure 6 – Frequency resolution enhanced by FFT-based measuring instrument 32
Figure 7 – Concept of magnetic field induced current measurements made with the loop antenna system 34
Figure 8 – Measurement distance 36
Figure 9 – Separation distance relative to the phase centre of an LPDA antenna 38
Figure 10 – Concept of electric field strength measurements made on an open-area test site (OATS) or semi-anechoic chamber (SAC) showing the direct and reflected rays arriving at the receiving antenna 39
Figure 11 – Position of CMAD for table-top equipment on OATS or in SAC 42
Figure 12 – Typical FAR site geometry, where a, b, c, e depend upon the room performance 43
Figure 13 – Typical test set-up for table-top equipment within the test volume of a FAR 44
Figure 14 – Typical test set-up for floor-standing equipment within the test volume of a FAR 45
Figure 15 – Positions of reference planes for uniform field calibration (top-view) 48
Figure 16 – Test set-up for table-top equipment 52
Figure 17 – Test set-up for table-top equipment – Top view 53
Figure 18 – Test set-up for floor-standing equipment 54
Figure 19 – Test set-up for floor-standing equipment – Top view 55
Figure 20 – Measurement method above 1 GHz, receive antenna in vertical polarization 57
Figure 21 – Illustration of height scan requirements for two different categories of EUTs 59
Figure 22 – Determination of the transition distance 69
Figure 23 – Substitution method set-up geometries for: a) measurement, b) calibration 71
Figure 24 – Process to give reduction of measurement time 73
Figure A.1 – Flow diagram for the selection of bandwidths and detectors and the estimated measurement errors due to that selection 80
Figure A.2 – Relative difference in adjacent emission amplitudes during preliminary testing 82
Figure A.3 – Disturbance by an unmodulated signal (dotted line) 83

Figure A.4 – Disturbance by an amplitude-modulated signal (dotted line) 83

Figure A.5 – Indication of an amplitude-modulated signal as a function of modulation frequency with the QP detector in CISPR bands B, C and D 84

Figure A.6 – Indication of a pulse-modulated signal (pulse width 50 μs) as a function of pulse repetition frequency with peak, QP and average detectors 85

Figure A.7 – Disturbance by a broadband signal (dotted line) 85

Figure A.8 – Unmodulated EUT disturbance (dotted line) 86

Figure A.9 – Amplitude-modulated EUT disturbance (dotted line) 87

Figure A.10 – Increase of peak value with superposition of two unmodulated signals 88

Figure A.11 – Determination of the amplitude of the disturbance signal by means of the amplitude ratio d and the factor i (see Equation (A.3) and Equation (A.6)) 89

Figure A.12 – Increase of average indication measured with a real receiver and calculated from Equation (A.8) 90

Figure C.1 – Weighting function of a 10 ms pulse for peak (PK) and average detections with (CISPR AV) and without (AV) peak reading: meter time constant 160 ms 97

Figure C.2 – Weighting functions of a 10 ms pulse for peak (PK) and average detections with (CISPR AV) and without (AV) peak reading: meter time constant 100 ms 97

Figure C.3 – Example of weighting functions (of a 1 Hz pulse) for peak (PK) and average detections as a function of pulse width: meter time constant 160 ms 98

Figure C.4 – Example of weighting functions (of a 1 Hz pulse) for peak (PK) and average detections as a function of pulse width: meter time constant 100 ms 98

Figure D.1 – Example of APD measurement Method 1 for fluctuating disturbances 99

Figure D.2 – Example of APD measurement Method 2 for fluctuating disturbances 100

Table 1 – Minimum measurement times for the four CISPR bands 23

Table 2 – Minimum scan times for the three CISPR bands with peak and quasi-peak detectors 23

Table 3 – Applicable frequency ranges and document references for CISPR radiated emission test sites and test methods 33

Table 4 – Minimum dimension of w (w_{min}) 58

Table 5 – Example values of w for three antenna types 59

Table 6 – Horizontal polarization correction factors as a function of frequency 69

Table 7 – Recommended antenna heights to guarantee signal interception (for pre-scan) in the frequency range 30 MHz to 1 000 MHz 75

Table A.1 – Combinations of EUT disturbance and ambient emissions 79

Table A.2 – Measurement error depending on the detector type and on the combination of ambient and disturbing signal spectra 91

Table C.1 – Pulse suppression factors and scan rates for a 100 Hz video bandwidth 96

Table C.2 – Meter time constants and the corresponding video bandwidths and minimum scan times 96

Table E.1 – Maximum amplitude difference between peak and quasi-peak detected signals 101

INTERNATIONAL ELECTROTECHNICAL COMMISSION

INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE

_____

SPECIFICATION FOR RADIO DISTURBANCE AND IMMUNITY MEASURING APPARATUS AND METHODS –

Part 2-3: Methods of measurement of disturbances and immunity – Radiated disturbance measurements

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard CISPR 16-2-3 has been prepared by CISPR subcommittee A: Radio-interference measurements and statistical methods.

This fourth edition edition cancels and replaces the third edition published in 2010, its Amendment 1:2010 and its Amendment 2:2014. This edition constitutes a technical revision.

This edition includes the following significant technical change with respect to the previous edition: addition of content on correction of the electric field strength to account for phase centre of log-periodic dipole array antennas.

It has the status of a basic EMC publication in accordance with IEC Guide 107, *Electromagnetic compatibility – Guide to the drafting of electromagnetic compatibility publications.*

The text of this standard is based on the following documents:

FDIS	Report on voting
CISPR/A/1176A/FDIS	CISPR/A/1182/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the CISPR 16 series, published under the general title *Specification for radio disturbance and immunity measuring apparatus and methods,* can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

SPECIFICATION FOR RADIO DISTURBANCE AND IMMUNITY MEASURING APPARATUS AND METHODS –

Part 2-3: Methods of measurement of disturbances and immunity – Radiated disturbance measurements

1 Scope

This part of CISPR 16 specifies the methods of measurement of radiated disturbance phenomena in the frequency range of 9 kHz to 18 GHz. The aspects of measurement uncertainty are specified in CISPR 16-4-1 and CISPR 16-4-2.

NOTE In accordance with IEC Guide 107 [13][1], CISPR 16-2-3 is a basic EMC publication for use by product committees of the IEC. As stated in Guide 107, product committees are responsible for determining the applicability of the EMC standard. CISPR and its subcommittees are prepared to co-operate with product committees in the evaluation of the value of particular EMC tests for specific products.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

CISPR 14-1:2016, *Electromagnetic compatibility – Requirements for household appliances, electric tools and similar apparatus – Part 1: Emission*

CISPR 16-1-1, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-1: Radio disturbance and immunity measuring apparatus – Measuring apparatus*

CISPR 16-1-2:2014, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-2: Radio disturbance and immunity measuring apparatus – Coupling devices for conducted disturbance measurements*

CISPR 16-1-4:2010, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-4: Radio disturbance and immunity measuring apparatus – Antennas and test sites for radiated disturbance measurements*
CISPR 16-1-4:2010/AMD1:2012

CISPR 16-2-1:2014, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 2-1: Methods of measurement of disturbances and immunity – Conducted disturbance measurements*

CISPR TR 16-4-1, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 4-1: Uncertainties, statistics and limit modelling – Uncertainties in standardized EMC tests*

CISPR 16-4-2, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 4-2: Uncertainties, statistics and limit modelling – Measurement instrumentation uncertainty*

---

1 Numbers in square brackets refer to the Bibliography.