BS ISO 22479:2019



BSI Standards Publication

Corrosion of metals and alloys — Sulfur dioxide test in a humid atmosphere (fixed gas method)

bsi.

National foreword

This British Standard is the UK implementation of ISO 22479:2019.

The UK participation in its preparation was entrusted to Technical Committee ISE/NFE/8, Corrosion of metals and alloys.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2019
Published by BSI Standards Limited 2019

ISBN 978 0 580 98868 4

ICS 77.060

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 May 2019.

Amendments/corrigenda issued since publication

Date	Text affected

BS ISO 22479:2019

INTERNATIONAL STANDARD

ISO 22479

First edition
2019-05-24

Corrosion of metals and alloys — Sulfur dioxide test in a humid atmosphere (fixed gas method)

Corrosion des métaux et alliages — Essai au dioxyde de soufre en atmosphère humide (méthode avec volume fixe de gaz)

Reference number
ISO 22479:2019(E)

© ISO 2019



COPYRIGHT PROTECTED DOCUMENT

© ISO 2019, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword ..... **iv**
Introduction ..... **v**
1 Scope **1**
2 Normative references **1**
3 Terms and definitions **1**
4 Principle **1**
5 Apparatus **1**
5.1 Component protection. 1
5.2 Test cabinet. 2
5.3 Source of sulfur dioxide. 3
5.4 Conditioning of a new cabinet. 3
6 Test specimens **3**
6.1 General 3
6.2 Dimensions 3
6.3 Preparation 3
6.3.1 Metals and alloys 3
6.3.2 Paints and varnishes 3
6.4 Arrangement of the test specimens 4
7 Test conditions **4**
7.1 Test cycles 4
7.2 Test duration 5
8 Procedure **6**
8.1 Introduction of water 6
8.2 Arrangement of the test specimens 6
8.3 Introduction of sulfur dioxide 6
8.4 Heating the test cabinet 6
8.5 Introduction of standard atmosphere 6
8.6 Replacement of water and sulfur dioxide 6
8.7 Cleaning of test specimens after test 6
8.7.1 General 6
8.7.2 Metals and alloys, metallic and non-organic coating test specimens 6
8.7.3 Organic coating test specimens 7
8.8 Performance check 7
9 Evaluation **7**
10 Test report **7**
Annex A (informative) **Another example of a test cabinet** **9**
Annex B (informative) **Performance check** **10**
Annex C (informative) **Supplemental information** **12**
Bibliography **14**

© ISO 2019 – All rights reserved

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 156, *Corrosion of metals and alloys*.

This first edition of ISO 22479 cancels and replaces ISO 3231:1993 and ISO 6988:1985, which have been combined and technically revised. The main changes compared with the previous edition are as follows:

— the method of generating sulfur dioxide from reagents has been deleted because of the risk of exposure to toxic chemicals.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

© ISO 2019 – All rights reserved

Introduction

A humid atmosphere containing sulfur dioxide induces corrosion of many metals.

The results obtained in this document should not be regarded as a direct guide to the corrosion resistance of the tested materials in all environments where these materials may be used. Similarly, performances of different materials in this document should not be taken as a direct guide to the relative corrosion resistance of these materials in service.

It is appropriate to test only the same corrosion protection systems at the same time in one test procedure, because an interaction between samples can't be prevented. When testing different corrosion protection systems with different materials, it should be taken into account that the influence of sulfur dioxide often can be different.

The term “fixed gas method” means that at the beginning of the test a fixed volume of gas is introduced into a cabinet of fixed volume.

© ISO 2019 – All rights reserved

This page deliberately left blank

INTERNATIONAL STANDARD **ISO 22479:2019**

Corrosion of metals and alloys — Sulfur dioxide test in a humid atmosphere (fixed gas method)

WARNING — This document does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this document to establish appropriate safety and health practices.

1 Scope

This document specifies a method for assessing the resistance of materials or products to a humid atmosphere containing sulfur dioxide.

This method is applicable to testing metals and alloys, metallic and non-organic coatings and organic coatings.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1514, *Paints and varnishes — Standard panels for testing*

ISO 2808, *Paints and varnishes — Determination of film thickness*

ISO 8044, *Corrosion of metals and alloys — Basic terms and definitions*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 8044 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at https://www.iso.org/obp

— IEC Electropedia: available at http://www.electropedia.org/

4 Principle

The test specimens are exposed to a humid atmosphere containing sulfur dioxide. The sulfur dioxide dissolved by the moisture condenses on the test specimen surface and causes corrosion.

5 Apparatus

5.1 Component protection.

All components in contact with sulfur dioxide in a humid atmosphere shall be made of corrosion resistant materials, and shall themselves not emit any gas or vapour likely to influence corrosion of the test specimens.

© ISO 2019 – All rights reserved